

09/743933

## ROBOTIC SYSTEM

*Ins > B2*

The present invention relates to robotic systems and, more particularly to a mobile robotic system capable of movement over a surface and capable of treating the surface.

*Ins B3 >*

Conventionally robotic systems, or robots, of this type may be described as semi-autonomous, i.e. self-propelling but relying for navigational guidance on transmitters, receivers and sensors to establish a coordinate system by which the robot navigates, in effect learning the location of obstacles within its field of movement. More recently it has been proposed to allow a robot to move without establishing a coordinate system, instead relying on the sensing of *ad hoc* stimuli to enable the robot to navigate around obstacles. For example, it has been proposed to provide a robotic vacuum cleaner operating along these lines. Self-navigational robotic systems of this type are referred to as autonomous robots.

However, robots of these types, often intended for operation in a domestic environment, need a control system which is capable of allowing the robot to move around its environment in safety and therefore additionally need some sort of collision detection system which is capable of providing information on collisions or impending collisions to a control system capable of acting very quickly to prevent the collision or else to minimise the impact, and to perform collision avoidance by re-orienting the robot before further movement. Unfortunately, on-board processing power is inevitably limited by cost constraints in particular and therefore present systems, to avoid be prohibitively expensive, have relatively limiting navigational abilities which result, in use, in the robot tracing a path which involves passing over the same areas of the surface on plural occasions. Whilst this may not be problematic in say a vacuum cleaner, if the robot has the

function of treating the surface in other ways, then such redundant movement may result in over-treatment of the surface which is not only wasteful of the product used for the treatment (a serious problem where the payload is restricted), but may also damage the surface or otherwise actually be harmful.

1484 7 The present invention is aimed at providing a self-propelled robot which can overcome such problems.

According to the present invention, there is provided a self-propelled robot for movement over a surface to be treated, the robot comprising

a power supply;

a traction mechanism receiving power from the power supply, for moving the robot over the surface;

a mechanism for controllably depositing a fluent material on to the surface;

a plurality of navigation sensors providing signals for enabling the robot to navigate over the surface;

one or more detectors adapted to detect the presence of the material on the surface and provide signals indicative thereof; and

a control system receiving the signals from the sensors and detectors, for controlling the traction mechanism and the depositing mechanism in dependence upon the signals received from the sensors and detectors.

By detecting the application of the fluent material, which may be a liquid or gaseous fluid or else a flowable powder, the over-application of material can be avoided or minimised by either navigating the robot around areas already treated and/or by controlling the depositing mechanism to stop the deposit of material over such previously treated areas.

Material for treatment is preferably contained within a reservoir on the robot and may comprise suitable compositions for treatment of floors, carpets and other floor coverings. The robot may, if desired, also include

means for cleaning the floor or floor covering prior to treatment, for example in the form of a vacuum cleaning device.

The invention also includes a method of treating a surface using a robot as defined above. The treatment method may be used for various applications on carpets, and other floor coverings, such as cleaning, protective treatment, for example for stain and soil protection, fire protection, UV protection, wear resistance, dust mite control, anti microbial treatment and the like, as well as treatment to provide an aesthetic benefit such as odorization/deodorization. The treatment method may also find application on other surfaces such as synthetic floor coverings, ceramics or wood. As well as polishing hard surfaces, the robot may also be used to apply coatings to either enhance aesthetics or to act as a protective layer.

Thus, according to a further aspect of the invention, there is provided a method for controllably depositing a fluent material on to floors, carpets and other floor coverings using an autonomous, self propelled, deposition-sensing robot. The material deposited may, for example, be a carpet cleaning composition, a hard surface cleaning composition, or one of a number of compositions applied simultaneously, or successively, and may include a marker, the presence of which can be detected to provide detection of the extent of treatment material deposition. Such a marker may have a limited detection life, for example, 12, 24 or 48 hours.

Non-visible treatment may also be provided by the robot of the invention, for example, for odour control, antibacterial action of dust mite control.

15  
25  
35  
45  
55  
65  
75  
85  
95  
105  
115  
125  
135  
145  
155  
165  
175  
185  
195  
205  
215  
225  
235  
245  
255  
265  
275  
285  
295  
305  
315  
325  
335  
345  
355  
365  
375  
385  
395  
405  
415  
425  
435  
445  
455  
465  
475  
485  
495  
505  
515  
525  
535  
545  
555  
565  
575  
585  
595  
605  
615  
625  
635  
645  
655  
665  
675  
685  
695  
705  
715  
725  
735  
745  
755  
765  
775  
785  
795  
805  
815  
825  
835  
845  
855  
865  
875  
885  
895  
905  
915  
925  
935  
945  
955  
965  
975  
985  
995  
1005  
1015  
1025  
1035  
1045  
1055  
1065  
1075  
1085  
1095  
1105  
1115  
1125  
1135  
1145  
1155  
1165  
1175  
1185  
1195  
1205  
1215  
1225  
1235  
1245  
1255  
1265  
1275  
1285  
1295  
1305  
1315  
1325  
1335  
1345  
1355  
1365  
1375  
1385  
1395  
1405  
1415  
1425  
1435  
1445  
1455  
1465  
1475  
1485  
1495  
1505  
1515  
1525  
1535  
1545  
1555  
1565  
1575  
1585  
1595  
1605  
1615  
1625  
1635  
1645  
1655  
1665  
1675  
1685  
1695  
1705  
1715  
1725  
1735  
1745  
1755  
1765  
1775  
1785  
1795  
1805  
1815  
1825  
1835  
1845  
1855  
1865  
1875  
1885  
1895  
1905  
1915  
1925  
1935  
1945  
1955  
1965  
1975  
1985  
1995  
2005  
2015  
2025  
2035  
2045  
2055  
2065  
2075  
2085  
2095  
2105  
2115  
2125  
2135  
2145  
2155  
2165  
2175  
2185  
2195  
2205  
2215  
2225  
2235  
2245  
2255  
2265  
2275  
2285  
2295  
2305  
2315  
2325  
2335  
2345  
2355  
2365  
2375  
2385  
2395  
2405  
2415  
2425  
2435  
2445  
2455  
2465  
2475  
2485  
2495  
2505  
2515  
2525  
2535  
2545  
2555  
2565  
2575  
2585  
2595  
2605  
2615  
2625  
2635  
2645  
2655  
2665  
2675  
2685  
2695  
2705  
2715  
2725  
2735  
2745  
2755  
2765  
2775  
2785  
2795  
2805  
2815  
2825  
2835  
2845  
2855  
2865  
2875  
2885  
2895  
2905  
2915  
2925  
2935  
2945  
2955  
2965  
2975  
2985  
2995  
3005  
3015  
3025  
3035  
3045  
3055  
3065  
3075  
3085  
3095  
3105  
3115  
3125  
3135  
3145  
3155  
3165  
3175  
3185  
3195  
3205  
3215  
3225  
3235  
3245  
3255  
3265  
3275  
3285  
3295  
3305  
3315  
3325  
3335  
3345  
3355  
3365  
3375  
3385  
3395  
3405  
3415  
3425  
3435  
3445  
3455  
3465  
3475  
3485  
3495  
3505  
3515  
3525  
3535  
3545  
3555  
3565  
3575  
3585  
3595  
3605  
3615  
3625  
3635  
3645  
3655  
3665  
3675  
3685  
3695  
3705  
3715  
3725  
3735  
3745  
3755  
3765  
3775  
3785  
3795  
3805  
3815  
3825  
3835  
3845  
3855  
3865  
3875  
3885  
3895  
3905  
3915  
3925  
3935  
3945  
3955  
3965  
3975  
3985  
3995  
4005  
4015  
4025  
4035  
4045  
4055  
4065  
4075  
4085  
4095  
4105  
4115  
4125  
4135  
4145  
4155  
4165  
4175  
4185  
4195  
4205  
4215  
4225  
4235  
4245  
4255  
4265  
4275  
4285  
4295  
4305  
4315  
4325  
4335  
4345  
4355  
4365  
4375  
4385  
4395  
4405  
4415  
4425  
4435  
4445  
4455  
4465  
4475  
4485  
4495  
4505  
4515  
4525  
4535  
4545  
4555  
4565  
4575  
4585  
4595  
4605  
4615  
4625  
4635  
4645  
4655  
4665  
4675  
4685  
4695  
4705  
4715  
4725  
4735  
4745  
4755  
4765  
4775  
4785  
4795  
4805  
4815  
4825  
4835  
4845  
4855  
4865  
4875  
4885  
4895  
4905  
4915  
4925  
4935  
4945  
4955  
4965  
4975  
4985  
4995  
5005  
5015  
5025  
5035  
5045  
5055  
5065  
5075  
5085  
5095  
5105  
5115  
5125  
5135  
5145  
5155  
5165  
5175  
5185  
5195  
5205  
5215  
5225  
5235  
5245  
5255  
5265  
5275  
5285  
5295  
5305  
5315  
5325  
5335  
5345  
5355  
5365  
5375  
5385  
5395  
5405  
5415  
5425  
5435  
5445  
5455  
5465  
5475  
5485  
5495  
5505  
5515  
5525  
5535  
5545  
5555  
5565  
5575  
5585  
5595  
5605  
5615  
5625  
5635  
5645  
5655  
5665  
5675  
5685  
5695  
5705  
5715  
5725  
5735  
5745  
5755  
5765  
5775  
5785  
5795  
5805  
5815  
5825  
5835  
5845  
5855  
5865  
5875  
5885  
5895  
5905  
5915  
5925  
5935  
5945  
5955  
5965  
5975  
5985  
5995  
6005  
6015  
6025  
6035  
6045  
6055  
6065  
6075  
6085  
6095  
6105  
6115  
6125  
6135  
6145  
6155  
6165  
6175  
6185  
6195  
6205  
6215  
6225  
6235  
6245  
6255  
6265  
6275  
6285  
6295  
6305  
6315  
6325  
6335  
6345  
6355  
6365  
6375  
6385  
6395  
6405  
6415  
6425  
6435  
6445  
6455  
6465  
6475  
6485  
6495  
6505  
6515  
6525  
6535  
6545  
6555  
6565  
6575  
6585  
6595  
6605  
6615  
6625  
6635  
6645  
6655  
6665  
6675  
6685  
6695  
6705  
6715  
6725  
6735  
6745  
6755  
6765  
6775  
6785  
6795  
6805  
6815  
6825  
6835  
6845  
6855  
6865  
6875  
6885  
6895  
6905  
6915  
6925  
6935  
6945  
6955  
6965  
6975  
6985  
6995  
7005  
7015  
7025  
7035  
7045  
7055  
7065  
7075  
7085  
7095  
7105  
7115  
7125  
7135  
7145  
7155  
7165  
7175  
7185  
7195  
7205  
7215  
7225  
7235  
7245  
7255  
7265  
7275  
7285  
7295  
7305  
7315  
7325  
7335  
7345  
7355  
7365  
7375  
7385  
7395  
7405  
7415  
7425  
7435  
7445  
7455  
7465  
7475  
7485  
7495  
7505  
7515  
7525  
7535  
7545  
7555  
7565  
7575  
7585  
7595  
7605  
7615  
7625  
7635  
7645  
7655  
7665  
7675  
7685  
7695  
7705  
7715  
7725  
7735  
7745  
7755  
7765  
7775  
7785  
7795  
7805  
7815  
7825  
7835  
7845  
7855  
7865  
7875  
7885  
7895  
7905  
7915  
7925  
7935  
7945  
7955  
7965  
7975  
7985  
7995  
8005  
8015  
8025  
8035  
8045  
8055  
8065  
8075  
8085  
8095  
8105  
8115  
8125  
8135  
8145  
8155  
8165  
8175  
8185  
8195  
8205  
8215  
8225  
8235  
8245  
8255  
8265  
8275  
8285  
8295  
8305  
8315  
8325  
8335  
8345  
8355  
8365  
8375  
8385  
8395  
8405  
8415  
8425  
8435  
8445  
8455  
8465  
8475  
8485  
8495  
8505  
8515  
8525  
8535  
8545  
8555  
8565  
8575  
8585  
8595  
8605  
8615  
8625  
8635  
8645  
8655  
8665  
8675  
8685  
8695  
8705  
8715  
8725  
8735  
8745  
8755  
8765  
8775  
8785  
8795  
8805  
8815  
8825  
8835  
8845  
8855  
8865  
8875  
8885  
8895  
8905  
8915  
8925  
8935  
8945  
8955  
8965  
8975  
8985  
8995  
9005  
9015  
9025  
9035  
9045  
9055  
9065  
9075  
9085  
9095  
9105  
9115  
9125  
9135  
9145  
9155  
9165  
9175  
9185  
9195  
9205  
9215  
9225  
9235  
9245  
9255  
9265  
9275  
9285  
9295  
9305  
9315  
9325  
9335  
9345  
9355  
9365  
9375  
9385  
9395  
9405  
9415  
9425  
9435  
9445  
9455  
9465  
9475  
9485  
9495  
9505  
9515  
9525  
9535  
9545  
9555  
9565  
9575  
9585  
9595  
9605  
9615  
9625  
9635  
9645  
9655  
9665  
9675  
9685  
9695  
9705  
9715  
9725  
9735  
9745  
9755  
9765  
9775  
9785  
9795  
9805  
9815  
9825  
9835  
9845  
9855  
9865  
9875  
9885  
9895  
9905  
9915  
9925  
9935  
9945  
9955  
9965  
9975  
9985  
9995  
10005  
10015  
10025  
10035  
10045  
10055  
10065  
10075  
10085  
10095  
10105  
10115  
10125  
10135  
10145  
10155  
10165  
10175  
10185  
10195  
10205  
10215  
10225  
10235  
10245  
10255  
10265  
10275  
10285  
10295  
10305  
10315  
10325  
10335  
10345  
10355  
10365  
10375  
10385  
10395  
10405  
10415  
10425  
10435  
10445  
10455  
10465  
10475  
10485  
10495  
10505  
10515  
10525  
10535  
10545  
10555  
10565  
10575  
10585  
10595  
10605  
10615  
10625  
10635  
10645  
10655  
10665  
10675  
10685  
10695  
10705  
10715  
10725  
10735  
10745  
10755  
10765  
10775  
10785  
10795  
10805  
10815  
10825  
10835  
10845  
10855  
10865  
10875  
10885  
10895  
10905  
10915  
10925  
10935  
10945  
10955  
10965  
10975  
10985  
10995  
11005  
11015  
11025  
11035  
11045  
11055  
11065  
11075  
11085  
11095  
11105  
11115  
11125  
11135  
11145  
11155  
11165  
11175  
11185  
11195  
11205  
11215  
11225  
11235  
11245  
11255  
11265  
11275  
11285  
11295  
11305  
11315  
11325  
11335  
11345  
11355  
11365  
11375  
11385  
11395  
11405  
11415  
11425  
11435  
11445  
11455  
11465  
11475  
11485  
11495  
11505  
11515  
11525  
11535  
11545  
11555  
11565  
11575  
11585  
11595  
11605  
11615  
11625  
11635  
11645  
11655  
11665  
11675  
11685  
11695  
11705  
11715  
11725  
11735  
11745  
11755  
11765  
11775  
11785  
11795  
11805  
11815  
11825  
11835  
11845  
11855  
11865  
11875  
11885  
11895  
11905  
11915  
11925  
11935  
11945  
11955  
11965  
11975  
11985  
11995  
12005  
12015  
12025  
12035  
12045  
12055  
12065  
12075  
12085  
12095  
12105  
12115  
12125  
12135  
12145  
12155  
12165  
12175  
12185  
12195  
12205  
12215  
12225  
12235  
12245  
12255  
12265  
12275  
12285  
12295  
12305  
12315  
12325  
12335  
12345  
12355  
12365  
12375  
12385  
12395  
12405  
12415  
12425  
12435  
12445  
12455  
12465  
12475  
12485  
12495  
12505  
12515  
12525  
12535  
12545  
12555  
12565  
12575  
12585  
12595  
12605  
12615  
12625  
12635  
12645  
12655  
12665  
12675  
12685  
12695  
12705  
12715  
12725  
12735  
12745  
12755  
12765  
12775  
12785  
12795  
12805  
12815  
12825  
12835  
12845  
12855  
12865  
12875  
12885  
12895  
12905  
12915  
12925  
12935  
12945  
12955  
12965  
12975  
12985  
12995  
13005  
13015  
13025  
13035  
13045  
13055  
13065  
13075  
13085  
13095  
13105  
13115  
13125  
13135  
13145  
13155  
13165  
13175  
13185  
13195  
13205  
13215  
13225  
13235  
13245  
13255  
13265  
13275  
13285  
13295  
13305  
13315  
13325  
13335  
13345  
13355  
13365  
13375  
13385  
13395  
13405  
13415  
13425  
13435  
13445  
13455  
13465  
13475  
13485  
13495  
13505  
13515  
13525  
13535  
13545  
13555  
13565  
13575  
13585  
13595  
13605  
13615  
13625  
13635  
13645  
13655  
13665  
13675  
13685  
13695  
13705  
13715  
13725  
13735  
13745  
13755  
13765  
13775  
13785  
13795  
13805  
13815  
13825  
13835  
13845  
13855  
13865  
13875  
13885  
13895  
13905  
13915  
13925  
13935  
13945  
13955  
13965  
13975  
13985  
13995  
14005  
14015  
14025  
14035  
14045  
14055  
14065  
14075  
14085  
14095  
14105  
14115  
14125  
14135  
14145  
14155  
14165  
14175  
14185  
14195  
14205  
14215  
14225  
14235  
14245  
14255  
14265  
14275  
14285  
14295  
14305  
14315  
14325  
14335  
14345  
14355  
14365  
14375  
14385  
14395  
14405  
14415  
14425  
14435  
14445  
14455  
14465  
14475  
14485  
14495  
14505  
14515  
14525  
14535  
14545  
14555  
14565  
14575  
14585  
14595  
14605  
14615  
14625  
14635  
14645  
14655  
14665  
14675  
14685  
14695  
14705  
14715  
14725  
14735  
14745  
14755  
14765  
14775  
14785  
14795  
14805  
14815  
14825  
14835  
14845  
14855  
14865  
14875  
14885  
14895  
14905  
14915  
14925  
14935  
14945  
14955  
14965  
14975  
14985  
14995  
15005  
15015  
15025  
15035  
15045  
15055  
15065  
15075  
15085  
15095  
15105  
15115  
15125  
15135  
15145  
15155  
15165  
15175  
15185  
15195  
15205  
15215  
15225  
15235  
15245  
15255  
15265  
15275  
15285  
15295  
15305  
15315  
15325  
15335  
15345  
15355  
15365  
15375  
15385  
15395  
15405  
15415  
15425  
15435  
15445  
15455  
15465  
15475  
15485  
15495  
15505  
15515  
15525  
15535  
15545  
15555  
15565  
15575  
15585  
15595  
15605  
15615  
15625  
15635  
15645  
15655  
15665  
15675  
15685  
15695  
15705  
15715  
15725  
15735  
15745  
15755  
15765  
15775  
15785  
15795  
15805  
15815  
15825  
15835  
15845  
15855  
15865  
15875  
15885  
15895  
15905  
15915  
15925  
15935  
15945  
15955  
15965  
15975  
15985  
15995  
16005  
16015  
16025  
16035  
16045  
16055  
16065  
16075  
16085  
16095  
16105  
16115  
16125  
16135  
16145  
16155  
16165  
16175  
16185  
16195  
16205  
16215  
16225  
16235  
16245  
16255  
16265  
16275  
16285  
16295  
16305  
16315  
16325  
16335  
16345  
16355  
16365  
16375  
16385  
16395  
16405  
16415  
16425  
16435  
16445  
16455  
16465  
16475  
16485  
16495  
16505  
16515  
16525  
16535  
16545  
16555  
16565  
16575  
16585  
16595  
16605  
16615  
16625  
16635  
16645  
16655  
16665  
16675  
16685  
16695  
16705  
16715  
16725  
16735  
16745  
16755  
16765  
16775  
16785  
16795  
16805  
16815  
16825  
16835  
16845  
16855  
16865  
16875  
16885  
16895  
16905  
16915  
16925  
16935  
16945  
16955  
16965  
16975  
16985  
16995  
17005  
17015  
17025  
17035  
17045  
17055  
17065  
17075  
17085  
17095  
17105  
17115  
17125  
17135  
17145  
17155  
17165  
17175  
17185  
17195  
17205  
17215  
17225  
17235  
17245  
17255  
17265  
17275  
17285  
17295  
17305  
17315  
17325  
17335  
17345  
17355  
17365  
17375  
17385  
17395  
17405  
17415  
17425  
17435  
17445  
17455  
17465  
17475  
17485  
17495  
17505  
17515  
17525  
17535  
17545  
17555  
17565  
17575  
17585  
17595  
17605  
17615  
17625  
17635  
17645  
17655  
17665  
17675  
17685  
17695  
17705  
17715  
17725  
17735  
17745  
17755  
17765  
17775  
17785  
17795  
17805  
17815  
17825  
17835  
17845  
17855  
17865  
17875  
17885  
17895  
17905  
17915  
17925  
17935  
17945  
17955  
17965  
17975  
17985  
17995  
18005  
18015  
18025  
18035  
18045  
18055  
18065  
18075  
18085  
18095  
18105  
18115  
18125  
18135  
18145  
18155  
18165  
18175  
18185  
18195  
18205  
18215  
18225  
18235  
18245  
18255  
18265  
18275  
18285  
18295  
18305  
18315  
18325  
18335  
18345  
18355  
18365  
18375  
18385  
18395  
18405  
18415  
18425  
18435  
184

navigation sensors may include one or more collision sensors and/or proximity sensors. The collision sensors may include one or more lateral displacement sensors arranged on a peripheral sensor ring to provide 360° collision detection, and/or one or more vertical displacement sensors.

Utilising a generally circular shape together with a control regime which scans for the best direction of escape after the robot has become stuck (say in a corner) is especially advantageous. Furthermore, it may be additionally advantageous to detect the angle of any collision, in order to optimise the robots subsequent angle of movement away from the obstacle.

The traction mechanism preferably includes left and right, coaxially disposed drive wheels with corresponding drive motors which are preferably provided with pulse-width modulated drive signals.

For depositing material on the surface, an array of delivery ports, e.g. spray nozzles, may extend generally parallel with the drive wheel axis, preferably extending to the same lateral extent as the deposition detectors.

The detectors may comprise one or more sensors arranged to detect the edge of a section of previously deposited product. Suitable deposition detectors include one or more radiation sources and/or detectors, moisture detectors, reflectivity meters, conductivity meters etc. Detectors may be disposed laterally of the drive wheels, preferably forward thereof.

The robot further preferably comprises a control system for controlling deposition of the material dependent on the signals received from the one or more detectors and sensors. In preferred embodiments, the control system functions to control deposition of the material (e.g. to avoid or minimise over-application) by a combination of strategies comprising a) navigating the robot around previously-treated areas of the surface (referred to herein

as the 'navigation strategy'; and b) controlling the depositing mechanism to stop or reduce the deposit of fluent material on to the surface as the robot passes over such previously-treated areas (referred to herein as the 'deposition rate control strategy'). In practice, the control system arbitrates between the two strategies depending on the signals received from the navigation sensors and deposition detectors. The ability of the control system to arbitrate between the two strategies, for example to make a rapid judgment on whether to cross or navigate around previously-treated areas and whether to maintain, reduce or stop deposition accordingly, is an important feature for ensuring controlled deposition in the context of a fully autonomous robot designed to operate in the cluttered, unstructured and track-free environment typically found in domestic and institutional situations.

Alternatively, the control system can be designed to control deposition purely following a deposition rate control strategy, in other words, by controlling the depositing mechanism to stop or reduce the deposit of fluent material on to the surface as the robot passes over previously-treated areas. Of course, systems depending purely on deposition rate control require less complicated electronics than the preferred combined-strategy systems described above. On the other hand, single strategy systems can be less efficient in terms of the time required to complete the task in hand.

Preferably, the control system has a hierarchical architecture and includes one or more microprocessor controllers or microcontrollers for controlling higher-level functions, and providing higher-level instructions and a plurality of lower-level function modules adapted to receive signals from the sensors and detectors and to provide control signals in response thereto. The traction mechanism and product dispensing control signals are preferably issued to a traction mechanism controller and to

a product dispensing controller via a manifold or bus arranged to receive signal inputs from the microprocessor and a plurality of sub-processors each corresponding to a respective navigation sensor or the like. By this means, a distributed processing system can be employed to provide a high level of flexibility in control strategy, whilst allowing simple connection of the sub-processors, thus to reduce the complexity and expense of the control system. The various processors preferably include neural network functionality to provide behavioural characteristics appropriate to the chosen task of the robot, the behavioural characteristics of the processors preferably being moderated by a group of generic moderators providing necessary arbitration between the control instructions from the various processors. The higher-level functions preferably include one or more functions selected from determination of the robot being stuck, room size estimation, clutter level determination, and battery monitoring. The lower-level modules are preferably analog neural networks which provide, for example, edge follow and dispense control functions, together, preferably, with cliff sensing, collision detection, speed reduction and random movement functions.

One example of a self-propelled robot constructed in accordance with the present invention, and its method of operation, will now be described with reference to the accompanying drawings in which:-

Figure 1 is an underneath plan view of the robot;

Figure 2 is a functional diagram of the robot; and

Figures 3A-C illustrate neural net aspects of part of the robot's control system.

As can be seen from Figure 1, the robot of the present example is substantially circular in overall plan view. A simple plate-like chassis 1 supports both the mechanical and electrical components of the robot. The plate-like chassis 1 supports the body 2 of the robot on resilient

rubber mountings 3 which allow the body to move relative to the chassis when a force is applied, eg by collision with an object, to a sensor ring 20 which is disposed around the periphery of the body. Four displacement sensors 4 placed at 90° intervals around the robot measure lateral displacement of the body 2 relative to the chassis 1 and inform the control system of contact with an external object. The displacement sensors 4 are based on linear Hall Effect devices which produce a voltage which is proportional to the strength of the magnetic field in which they are immersed. Each sensor consists of a small permanent magnet mounted on the body shell support ring 20 and a Hall Effect device mounted on the main chassis 1. When the body moves with respect to the chassis (as happens during a collision) the voltage produced by the Hall Effect device varies and can be used to signal the control system that an object has been encountered. By examining the signals from all four sensors the angle and magnitude of the collision can be deduced. These sensors allow displacements in the order of 0.1 mm to be reliably detected. A fifth sensor 18, of the same type as the displacement sensors 4, measures vertical displacement of the body shell to accommodate forces produced by objects which are of insufficient height to cause lateral body movement. In an alternative construction, these sensors may be superseded by a single custom-built sensor which can measure lateral and vertical displacement simultaneously. Such an integrated sensor may be optical in nature utilising an array of photo detectors mounted on the chassis and a light source which is mounted on the body support ring.

A single forward facing time-of-flight ultrasound sensor 13 is mounted at the front of the robot and is used to allow the robot to gather more information regarding its surroundings than can be achieved by the displacement sensors 4 alone. This ultrasound sensor 13 is based on a Polaroid® ranging module Polaroid 6500 series sonar ranging

device, Polaroid reference 615077, the data from which is pre-processed by a dedicated unit 5 on which the sensor 13 is located. An ultrasonic sensor unit 5, containing the ultrasonic sensor 13 itself and a suitable electronic interface, are mounted on the body to provide proximity information to the robot's control system.

Left and right motors 6, 7 are provided to drive corresponding left and right wheels 8, 9 each with a soft rubber tyre, via an integral reduction gearbox, to provide motive power to the robot. A single castor 10 mounted at the rear of the robot completes the drive/movement system and allows the chassis to move forwards or backwards and rotate on the spot. Varying the rotational speed of the left and right motors 6, 7 allows the robot to be steered in any direction. The speed of the motors is controlled by pulse width modulating the voltages applied to the motors. This involves switching the motor current on and off very rapidly (100,000 times a second) and varying the ratio of 'on' time to 'off' time. This is a very efficient way to control the power to the motors and hence their speed.

Power for the robot, including the motors 6, 7 and the control system is provided by means of a battery pack 11 mounted on the chassis 1. To protect the components of the robot from tampering and from damage a cover or housing (not shown) is attached to the body 2 to house the robot components. In the preferred embodiment, this is part-spherical or dome-like in shape.

A row of spray nozzles 16 and a pump 115 (not shown in Figure 1) provide a means of dispensing treating fluid on to the surface to be treated and detectors 14,15,17 are provided to detect the presence of the treating fluid (or a suitable additional marker fluid). The three sensor units 14, 15, 17, one placed in front of each of the drive wheels and the third 17 placed centrally, emit light at a wavelength which excites a fluorescent dye in the product being detected. These sensor units incorporate a pair of



light sensitive devices positioned at 90° to the robot's direction of travel and spaced 20mm apart, which can detect light produced by the fluorescent dye. By examining the intensity of the light detected by these devices the edge of a section of previously deposited product can be detected and hence followed. In an alternative construction, the three sensor units 14, 15, 17 pass a small electrical current through the floor covering by virtue of an array of stainless steel contacts which are designed to glide over the floor covering surface. The conductivity of the floor covering will vary depending upon whether or not it has recently been sprayed with product. By examining the conductivity of the floor covering, the edge of previously deposited product can be detected and hence followed.

In an alternative construction, in which fluid is to be dispensed to an edge or corner, the positioning of the sprays is modified. The modification is such that the spray is able to dispense to the edge of the robot or beyond, for example, either by positioning nozzles at the very periphery of the underside or by additional nozzles which protrude from the casing and are directed such that they spray beyond the perimeter of the robot.

The robot's control system comprises various circuit boards and components which are not shown in Figure 1 in detail, but which are broadly indicated by reference numerals 12 in Figure 1.

The control system will now be described in further detail.

Two purposes of the control system of an autonomous mobile robot such as that of the example are to allow the robot to move within a physical environment in safety and to enable it to perform useful tasks. To do this the robot must be aware of its immediate surroundings and be able to react to particular circumstances in particular ways. A robot intended for an unconstrained domestic environment

needs to have certain basic skills, such as a collision detection skill, which might cause it to stop upon collision with an object and then take evasive action before resuming its previous activity.

In the case of collision detection, the sensors 4, 18, 13, which sense impacts with and proximity to objects, will inform the control system of the angle of impact and its force. The control system must react very quickly to this stimulus and prevent any further motion in this direction. A conventional approach to this problem would be to have a computer monitor the collision sensors and act upon the data to stop the motors and then perform some form of avoidance manoeuvre. This is perfectly feasible, but if the same computer is required simultaneously to perform other tasks, for example, such as in the present case, monitoring other sensors and performing navigational mathematics, it soon reaches a point where the speed and power of the on-board computer required becomes prohibitively expensive if reaction times are to be acceptable.

The alternative, adopted in the present invention, is to use discrete modules that perform functions in a way analogous to the reflexes of a biological organism. The advantage of this system are obvious: the main processor can merely issue high level commands such as move or turn and is left free to perform other abstract tasks.

This alternative is a form of hierarchical distributed processing and allows the control system to be composed of simple modules that together yield faster response times than a non-distributed system of the same cost. Another significant advantage of distributed processing is its inherent robustness. If a system employing a conventional single processor approach suffers a failure, it can leave the system in an unsafe state, which in the case of a robot might allow it to crash into objects or people. The distributed approach can be designed so as to have a much

greater degree of fault tolerance, rendering the occurrence of complete system failures much less likely.

Distributed processing can be implemented using conventional computers connected together by some form of network, but these tend to be expensive to design and implement. The approach adopted in the present invention is to simulate biological neural networks in real analogue hardware to provide a system that consists of behavioural modules, which are designed to perform individual tasks. These behaviours are managed by a simple micro controller, which performs higher level tasks such as mathematical functions to estimate room size or a strategy for escaping from under a table.

The control system 100 will now be described with reference to Figures 2 and 3. Figure 2 illustrates the functional relationship of the control system components.

The control behaviours used on the robot can be divided into two basic types, Low Level and High Level. Low Level behaviours are implemented in hardware as discrete neural blocks or modules 101-105, while High Level behaviours are software algorithms running on a micro controller 106.

The functions of the Low level behaviour modules 101-105 are now described in detail:-

Cliff - To prevent the robot falling down stairs it is equipped with four cliff detectors 21 which warn of vertical hazards and provide signals to the cliff behaviour module 101. The cliff detectors 21 are active infra red proximity sensors which comprise a modulated light source which emits a beam of infra red light directed at the target (in this case the floor), and an infra red detector which monitors the intensity of the light which is reflected. When the sensor is directed over a cliff the intensity of the reflected light decreases and the sensor informs the control system of the hazard. This behavioural function has

very high priority and when active operates to manoeuvre the robot away from the hazard and return it to a course which is modified to avoid cliff type drops.

**Edge Follow** - The Edge Follow module 104 provides a behavioural function which uses information from the sensors 14,15,17 which allow the robot to find the edge of a previously treated area (as described above) and to travel along that edge to produce a faster scan of the floor surface.

**Random** - In the absence of any edges the robot moves in a random direction under the action of a random movement module 114 until an object is encountered or the edge follow behaviour is activated.

**Collide** - The collision detection module 102 takes input from the displacement sensors 4,18 and operates so that upon encountering an obstacle the robot stops, reverses a small distance, then turns away from the object in a direction that depends upon the angle of impact, which is determined from the signals of the displacement sensors 4,18.

**Reduce Speed** - When an object is detected by the ultrasound sensor unit 5 within a pre-set range limit, the forward speed of the robot is reduced by the Reduce Speed module 103 to minimise the impact force generated when contact with the object occurs.

**Dispense** - A dispense control module 105 has inputs from a fluid level sensor 203 and sensors 14, 15, 17 via the Edge Follow module 104. If the UV sensors 14, 15, 17 report untreated carpet in the direction of travel the treatment chemical is dispensed until treated areas are encountered or fluid level reaches a lower limit.

High level behaviours are determined within the microcontroller 106 and comprise the following functional modules:-

**Stuck** - A routine 107 determines if there have been more than a chosen number of collisions in a select period and causes the robot to stop and use the ultrasound range finder 5, 13 to find the longest clear path and move in that direction. The robot will rotate on the spot, by operating the wheels 8, 9 in opposite directions, looking for the longest clear path. When the best direction is discovered the robot will move off in that direction.

**Estimate Room size** - By using statistics gathered from the ultrasound sensor 13 and measuring the time between collisions the routine 108 is able to estimate the area of the room. This is used to determine how long the robot should take to treat a particular room.

**Estimate clutter level** - By comparing estimates of room size against collisions per minute a routine 109 is able to deduce a factor describing the complexity of the room. This can then be used to modify the run time to allow for the level of clutter.

**Battery Monitor** - A battery monitor routine 110 checks the state of the battery by monitoring the output voltage and current. It uses this information to estimate how long the battery will be able to support the robot's systems before a re-charge is needed. When the monitor routine decides that the battery state is approaching the point where reliable operation is no longer possible, the user is warned by illumination of a battery low indicator. If the robot is allowed to continue to operate without being re-charged the monitor routine will shut the robot down in a safe and controlled fashion when power levels reach a predetermined point. Nickel Cadmium or Nickel Metal Hydride batteries require careful charging to ensure maximum capacity and life span and the monitor routine also controls the charging cycle of the battery to ensure that these needs are met.

Traditionally neural network designers have insisted that every neuron in a network is connected to every other neuron in that network. Whilst this allows the network the greatest level of flexibility, very many (even as high as 90%) of these connections will never be used. The present system allows pre-configured neural networks to be connected together in a much less complex way allowing the behaviour of the robot to dynamically adjust to the immediate environment in a continuous fashion.

This so-called "Manifold Architecture" comprises an analogue bus or manifold 111, connecting all the behaviour modules 101-105 and their associated actuators to each other. Four generic moderators arbitrate between the behaviours, and give rise to a prototype behaviour of their own which regulates the overall activity of the robot via a motor controller 112 and dispensing fluid pump controller 113 driving the pump 115. These generic moderators sum all the excitatory and inhibitory inputs and apply a non-linear transfer function to the results. The outputs from these moderators form the inputs to the motor controllers.

In order to explain the function of the manifold architecture, it is necessary to describe the basic neural aspects of the control system. Figures 3A-C will be referenced for this purpose.

A single neuron (see Fig. 3A) has three basic types of connections, excitatory inputs which cause the neuron to 'fire', inhibitory inputs which suppress activity and the output which represents the state of the neuron. Additionally neurons may have other properties such as Decay which causes the output to fall slowly over time, and Threshold which suppresses all output until the sum of all the input exceeds a certain level.

Figure 3B shows (by way of example) a simplified representation of the collide behaviour and the manifold system in neural notation.

The collision sensors 4 are represented in Fig. 3B as 1, 2, 3 and 4 and are buffered and normalised by sensor pre-processors 5, 6, 7 and 8. The outputs of the sensor pre-processors are each fed into a single neuron 9, 10, 11 and 12 configured as a pulse stretcher with a time constant of approximately 5 seconds. The outputs of these neurons are connected to the rest of the network formed by neurons 13 to 28 where the pattern of connections, and transfer characteristics of the neurons give rise to the behaviour itself. The outputs of this network are connected via the connections 41 to 48 to the manifold summators (generic moderators) 29 to 32 where the signals are summed and the outputs 37 to 40 form the inputs to the left and right motor controllers (not shown in this figure). Connections from another unspecified behaviour (of which there may be many) are shown as 50 to 57. Connection 49 is a subsumption input, which is used to disable the entire behaviour under control of the scheduler software running on a microcontroller or another higher priority neural behaviour. The sensor outputs are also made available to the microcontroller so that high level behaviours such as clutter level estimation may have access to any data produced.

In the event of a direct collision whilst travelling straight ahead the following is true:

The front collision sensor 1 produces a pulse as contact with an obstacle occurs. This pulse is amplified by the sensor pre-processing element 5 and passed to the input neuron 9. This neuron is configured to stretch the width of an input pulse (when that pulse exceeds a predetermined input threshold) to approximately 5 seconds. The output from the input neuron 9 is simultaneously fed to four other neurons 13, 14, 15 and 16. These 'hidden layer' neurons are configured to act as attenuators or in neural terms 'weights', and therefore change the

amplitude of the applied signals. Neurons 13 and 15 are set to produce an output level of 10 (maximum) when excited and the outputs are connected to the output neurons 22 and 26 which when excited apply signals to the manifold instructing the motors to stop moving forward. Neurons 14 and 16 are set to produce an output of 5 (half) when excited and their outputs are connected to the output neurons 23 and 27 which when excited apply signals to the manifold instructing the motors to move the robot backwards. This part of the behaviour itself, would theoretically lead to a situation where the robot would repeatedly collide and retreat in a straight line from an obstacle, but inherent inaccuracies in the control system and drive mechanics coupled with the fact that the probability of a perfect head on collision is remote, means that the other collision strategies which involve the left and right sensors, will cause the robot to turn as it reverses from an obstacle and produces a useful behaviour.

The manifold function will now be described in detail with reference to Fig. 3C. The manifold as it's name implies brings together all the output from the robots various neural behaviours, sums it together and provides the inputs to the motor controllers. Fig. 3C shows the section which controls the right hand motor controller; the left hand section is identical.

Connection 41 is effectively the 'Go forward right' input and 42 is 'Don't go forward right'. These two opposing inputs are fed into the excitatory and inhibitory inputs of neuron 29. If values of Go forward 6 and don't go forward 3 are applied simultaneously, neuron 29 outputs a value of 3, but if the values are reversed ie. Go forward 3 and don't go forward 6, neuron 29 produces 0. This is most important as it allows a behaviour to inhibit motion



in a particular direction without causing motion in the opposite direction.

Neuron 30 performs the same task as 29 except it's inputs are 'Go backwards' 43 and 'Don't go backwards' 44.

Neuron 29 is connected to the excitatory input of 33 which in turn drives the 'Go forward' input of the right hand motor controller via connection 37. Neurons 30 and 34 are connected to the 'Go backward' input of the right hand motor controller via connection 38. The motor controller sums these inputs so that Go forward 8 and Go Backward 4 simultaneously applied on connections 37 and 38 respectively will result in the right wheel rotating forward at a speed of 4.

Neurons 33 and 34 also have inhibitory connections where the forward signal path is connected to the reverse path and vice versa. This allows non-linear behaviour of the manifold and as the strength of these connections is increased, the robot becomes less likely to enter a stable state, where no motion occurs due to behaviours with conflicting interests asserting themselves simultaneously.

Further details of some of the various sensors and their operation will now be given:-

*Inc  
BIO* The ultrasound sensor unit 5 has a pre-processor which manages the sensor 13, providing timing pulses etc., and provides the high level behaviour with continuous 'range to target' data and a simple range warning to the reduce speed behaviour module 103. The continuous output is used by the stuck behaviour module 107 which rotates the robot through 360° whilst looking for a clear path down which the robot can escape and is also used by the room size and clutter estimation behaviour modules 109, 108.

To perform the task of dispensing the treatment compositions (for example, a carpet cleaning formulation, known per se, comprising of an aqueous solution of anionic surfactant, optionally together with a polycarboxylate soil

suspending agent) on to a surface, it is desirable to know which areas of the surface have already been treated.

A marker agent, added to the formulation in question, has characteristic properties such as absorption or emission of light at a known frequency, or fluorescent behaviour which can be detected by the robot. Examples of such markers are luminol, which can be made to react with hydrogen peroxide to emit light, and substituted coumarins such as 7-hydroxy or 4-methyl-7-hydroxy variants which are highly fluorescent but undergo ring opening reactions to form a non-fluorescent derivative.

For detection purposes, a light source and corresponding photodiode detectors 14, 15, 17 are placed left and right in front of the drive wheels 6,7 of the robot in order to detect said marker chemical and enable the control system to follow the edge of a previous pass. In this manner, a structured dispensing pattern can be established. Moreover, the detector can be linked, via a negative feedback system, to the dispensing array, thereby to avoid the deposition of formulation on to an area of surface that has already been treated. When no area of the floor can be found that has not been treated, the actual time taken is compared with data provided by the estimated room size behaviour module 108, and if the two are within acceptable limits, the treatment of the floor is deemed complete. The characteristic properties by which the marker is detected either decay within 24-48 hours of application (by aerial oxidation or photolytic decomposition) or, in the case of a two stage treatment method, a second chemical may be applied over the first, neutralising the characteristic properties of the marker chemical.

An alternative means of achieving this desired behaviour is to use moisture detection to identify areas of the surface which have already been treated. In this case, the inherent moisture of a liquid formulation is used to

detect treated surfaces via moisture sensing arrays which are positioned left and right in front of the drive wheels 6,7 of the robot. Again, this system can be used to enable the robot to follow the edge of a previous pass.

In cases where a hard floor surface is being treated (for example with an aqueous cleaning formulation comprising a mid chain-length non-ionic surfactant with carbonate citrate and caustic soda) the reflective properties of the floor may be used to detect which areas of floor have been treated. A high intensity light source directs light on to the floor where, following reflection, it is subsequently detected by a photodiode detector. These are positioned left and right in front of the drive wheels 6,7 of the robot. Again, this system can be used to enable the robot to follow the edge of a previous pass. In this case, the ability of a formulation to reduce the reflectivity of the floor is harnessed to enable its detection.